EMAC€ SP2258

€ • ¸ • ƒ „ … † ‡ ˆ

Westlake Chemical Corporation

€ • ¸ ƒ

Westlake EMAC€ SP2258 is a 17% EMA copolymer containing slip and antiblock. This resin is designed for blown or cast film, tie-layers, and extrusions where flexibility, compatibility, or low heat seal temperatures are required. SP2258 provides excellent adhesion to polyolefins, polyesters, and other polymers while providing outstanding low temperature performance.

‰ Š ‹ Œ				
• Ž	• • ‘ Ž š ›	’ ESCR(“ ” • – —)	† ‡ ˆ	‘ Ž ˜ ™
œ •	ž Ÿ ¦ § / ¨ © œ ª	¡	¢ £	¤ ¥
« ¬	- ®			
¯ ° ± ²	¡ ³ ´			

ˆ © Ž µ	¶ · ¸	¹ º »	¼ ½ ¾ ± ²
¾ ¿	0.943	g/cm•	ASTM D1505
À Á Â (À Ã Á Ä Å Â) (190,C/2.16 kg)	2.1	g/10 min	ASTM D1238
„ ‰ ¸ • ƒ Æ Ç	17.0	wt%	

È ¿	¶ · ¸	¹ º »	¼ ½ ¾ ± ²
É Ê È ¿ (Ë Ê D)	37		ASTM D2240

Ì Í Ž µ	¶ · ¸	¹ º »	¼ ½ ¾ ± ²
“ Î Ï ¿ 1 (Ð—)	12.0	MPa	ASTM D638
Ñ Ò Â 2 (Ð—)	730	%	ASTM D638

¡	¶ · ¸	¹ º »	¼ ½ ¾ ± ²
Ó Ô Õ Ç			ASTM D882
1% Ö Ó, MD : 38 ƒm, × Ø ¡	56.0	MPa	ASTM D882
1% Ö Ó, TD : 38 ƒm, × Ø ¡	59.0	MPa	ASTM D882
“ Î Ï ¿			ASTM D882
MD : Ð—, 38 ƒm, × Ø ¡	21.0	MPa	ASTM D882
TD : Ð—, 38 ƒm, × Ø ¡	16.0	MPa	ASTM D882
Ñ Ò Â			ASTM D882
MD : Ð—, 38 ƒm, × Ø ¡	330	%	ASTM D882
TD : Ð—, 38 ƒm, × Ø ¡	660	%	ASTM D882
Ù Ú Û Ü (38 ƒm, × Ø ¡)	300	g	ASTM D1709A
Ý Þ ß à á “ â Ï ¿			ASTM D1922
MD : 38 ƒm, × Ø ¡	53	g	ASTM D1922
TD : 38 ƒm, × Ø ¡	340	g	ASTM D1922
ã ä • ¿	70.0	,C	

å Ž µ	¶ · ¸	¹ º »	¼ ½ ¾ ± ²
æ ç • ¿	< -73.0	,C	ASTM D746
è é › ç • ¿	56.0	,C	ASTM D1525
À ê ë ¸ • ¿	82.0	,C	ASTM D3418

Ì Í Ž µ	¶ · ¸	¹ º »	¼ ½ ¾ ± ²
Ì Î ¿ (45,, 38.1 ƒm, × Ø ¡)	15		ASTM D2457
Ï ¿ (38.1 ƒm, × Ø ¡)	53	%	ASTM D1003

ð ñ	
1.	ò ó 4, 500 mm/min
2.	ò ó 4, 500 mm/min