EMAC€ SP2260

€ • ¸ • ƒ „ … † ‡ ˆ

Westlake Chemical Corporation

€ • ¸ ƒ

EMAC resins adhere to and are compatible with a wide range of materials including paper, polyolefins, oriented polyolefins, polyesters, ionomers, PVdC, unplasticized PVC and other polar polymers. For use as heat seal layer, adhesive layer, or modifier for cost/performance enhancement. They are soft, pliable and tough at ambient and freezing temperatures and exhibit excellent ESCR. These polymers exhibit high solids fillability and compatibility with a wide range of polymers. This facilitates their uses as bases for all-purpose concentrates for addition to a wide spectrum of polymers. EMAC resins process like LDPE. EMAC+ Specialty Copolymers are produced under patented technology: US Patent 5804675.

‰ Š ‹ Œ				
• Ž	• • ‘ Ž š ›	’ ESCR(“ ” • – —)	† ‡ ˆ	‘ Ž ˜ ™
œ •	ž Ÿ	¡	¢ £ / ¤ ¥ œ ¦	
§ ¨	© ª			
« ¬ - ®	ž Ÿ ¯ °			

ˆ ¥ Ž ±	² ³ ´	µ ¶ ·	¸ ¹ - ®
º »	0.944	g/cm€	ASTM D1505
¼½¾(¼ ¿ ½ À Á ¾) (190•C/2.16 kg)	2.1	g/10 min	ASTM D1238
„ ‰ ¸ • ƒ Â Ã	24.0	wt%	

Ä »	² ³ ´	µ ¶ ·	¸ ¹ - ®
ÅÆÄ » (ÇÆ D)	37		ASTM D2240

È É Ž ±	² ³ ´	µ ¶ ·	¸ ¹ - ®
“ Ê Ë » [1] (Ì —)	11.0	MPa	ASTM D638
Í Î ¾ [2] (Ì —)	840	%	ASTM D638

Ï Ž ±	² ³ ´	µ ¶ ·	¸ ¹ - ®
Ð Ñ • »	< -73.0	•C	ASTM D746
Ò Ó › Ñ • »	50.0	•C	ASTM D1525
¼Ô Õ ´ • »	77.0	•C	ASTM D3418

Ö ×	
1.	Ø Ù 4, 500 mm/min
2.	Ø Ù 4, 500 mm/min