

# EMAC€ SP2403

€ • , • f „ ... † ‡ ^

## Westlake Chemical Corporation

€ • , f

EMAC resins adhere to and are compatible with a wide range of materials including paper, polyolefins, oriented polyolefins, polyesters, ionomers, PVdC, unplasticized PVC and other polar polymers. For use as heat seal layer, adhesive layer, or modifier for cost/performance enhancement. They are soft, pliable and tough at ambient and freezing temperatures and exhibit excellent ESCR. These polymers exhibit high solids fillability and compatibility with a wide range of polymers. This facilitates their uses as bases for all-purpose concentrates for addition to a wide spectrum of polymers. They process like LDPE.

%Š < €				
• Ž	• ESCR(• ' ' " " )	† ‡ ^	• — —Ž ~	™ Ž š >
ž Ÿ	i	Φ Ε	¤ ¥	! \$ / ' © ž ª
« ¬ - ®	FDA 21 CFR 177.1520			
- °	± ²			
³ ´ µ ¶	Φ Ε · ¸			
~ © Ž ~	1 ° »		¼ ½ ¾	¿ À µ ¶
Á Â	0.945		g/cm³	ASTM D1505
Ã Ä Å (Ã Ä Å Ç È Å) (190°C/2.16 kg)	6.5		g/10 min	ASTM D1238
„ % , • f É Ê	24.0		wt%	
Ë Æ	1 ° »		¼ ½ ¾	¿ À µ ¶
Ï Í È Á (Í Í D)	34			ASTM D2240
« Í Ž ~	1 ° »		¼ ½ ¾	¿ À µ ¶
• Ñ Ò ¹ (Ò" )	8.00		MPa	ASTM D638
Ó Ô Å ² (Ò" )	670		%	ASTM D638
Õ Ž ~	1 ° »		¼ ½ ¾	¿ À µ ¶
Ö × Ø Å	< -73.0		•C	ASTM D746
Ù Ú • × Ø Å	44.0		•C	ASTM D1525
Û Ü » Ø Å	75.0		•C	ASTM D3418
Ý Þ				
1.	ß à 4, 500 mm/min			
2.	ß à 4, 500 mm/min			