Escor € 5000

Ethylene Acrylic Acid Copolymer Resin

ExxonMobil Chemical

€ • ¸ ƒ

Escor 5000 € • ¸ ƒ „ … † ‡ ˆ „ † ‡ ‰ „ … Š ‹ . Œ • Ž • • ‹ ƒ ‘ ’ “ ” , • – ,— ˜ ™ , š › ,œ • ‰ ž Ÿ ¡ . ¢ £ ¤ “ ” ¡ ¥ • ‹ ’ ‰ ¤ ˆ „ ¥ ¦ § ¨ © ª « ‰ ª « ¬ - ª « ® ¥ ¯ ° ± ‹ ² ¥ … ³ ´ µ . ¶ ™ · ‘ ¸ ¥ • ‹ ’ © ‹ ¹ .

“ º » ¼			
½ ¾ ’ ¿	À Á Â	Ã Ä Å	Æ Ç È É
Ê Ë Ì (Ê ¹ Ë Í Î Ì) (190€C/2.16 kg)	8.2	g/10 min	ASTM D1238
Ï « - Ð Ñ	6.0	wt%	ExxonMobil Method

É Ò Ó Ô

Õ Ö × Ø Ù Ú Û Ü Ý ¸ ‹ Þ » ¼ (ß à : FDA,EU,HPFB), á ¤ â ã ä å æ ç è é ê ë ì í î ï . º ð Ú ñ ò Ø ó ô Ý ¸ · õ ¸ , ö ñ Ý Ø ÷ ø ù ú Ý ¸ · õ ¸

„ û ü Ô

Excellent results are obtained in extrusion coating at 260€C - 280€C (500€F - 536€F) temperature range. Processing temperatures above 300€C (572€F) may cause resin degradation. To minimize corrosion risk, all exposed metal surfaces in the extruder and die should be made from corrosion resistant metals or nickel/chrome plated. ESCOR should be fed into the extruder after LDPE of a similar or higher melt index. Machines should always be completely purged with LDPE or a suitable cleaning compound before shutdown.