Escor € 5020

Ethylene Acrylic Acid Copolymer Resin

ExxonMobil Chemical

€ • , ƒ

Escor 5020 € • , ƒ „ … † ‡ ˆ ‰ „ † ‡ . Š ‹ Œ • Ž • ƒ • ‘ ’ “ ” • , – — ˜ , ™ š , › œ ˆ • ž Ÿ . ¡ ¢ £ ’ “ Ÿ ¤ Ž • ‘ ˆ £ ‰ „ ¤ ¥ ¦ § ¨ © ª ˆ © ª « ¬ © ª - ¤ ® ¯ ° • ± ¤ … ² ³ ´

’ µ ¶ ·			
¸ ¹ ‘ º	» ¼ ½	¾ ¿ À	Á Â Ã Ä
ÅÆÇ(Å ÈÆÉ ÊÇ) (190€C/2.16 kg)	8.3	g/10 min	ASTM D1238
Ë ª ¬ Ì Í	7.5	wt%	ExxonMobil Method

Ä Î Ï Ð

Ñ Ò Ó Ô Õ Ö × Ø Ù , • Ú ¶ · (Û Ü:FDA,EU,HPFB), Ý £ Þ ß à á â ã ä å æ ç è é Ÿ ê ë . µ ì Ö í î Ô ï ð Ù , ñ ò , , ó í Ù Ô ô õ ö ÷ Ù , ñ ò ,

„ ø ù Ð

Excellent results are obtained in extrusion coating at 260€C - 280€C (500€F - 536€F) temperature range. Processing temperatures above 300€C (572€F) may cause resin degradation. To minimize corrosion risk, all exposed metal surfaces in the extruder and die should be made from corrosion resistant metals or nickel/chrome plated. ESCOR should be fed into the extruder after LDPE of a similar or higher melt index. Machines should always be completely purged with LDPE or a suitable cleaning compound before shutdown.