ALCUDIA€ EVA PA-470

€ • , ƒ € • „ … †

REPSOL

€ • , ƒ

EVA resin ALCUDIA€ PA-470 is recommended for adhesive formulations, sealants and solution coatings. It contains antioxidant and free flowing agent.
TYPICAL APPLICATIONS
Hot melt adhesives
Pressure sensitive adhesive coatings
Wood primers and sealers
Inks formulations
Recommended melt temperature below 200•C to avoid the decomposition of the polymer. Processing conditions should be optimised for each production line.

‡ ˆ ‰ Š			
‹ Œ •	Ž • • ‘	’ “ •	
” ‘	Ž • • ‘		
• –	— ˜ •	™ š › •	œ • •

† ž ‘ Ÿ	¡ ¢	£ ¤ ¥	¦ § ¨ ©
— ª (23•C)	0.969	g/cm,	ISO 1183
« ’ ¬ (« - ’ ® ¯ ¬) (190•C/2.16 kg)	55	g/10 min	ISO 1133
, ƒ € • ° ±	40.0	wt%	

² a	¡ ¢	£ ¤ ¥	¦ § ¨ ©
³ ´ ² ª (µ ´ A)	51		ISO 868

¶ · ‘ Ÿ	¡ ¢	£ ¤ ¥	¦ § ¨ ©
¸ ¹ › º (» ¼)	7.00	MPa	ISO 527-2
¸ ¹ › ½ (» ¼)	940	%	ISO 527-2

¾ ‘ Ÿ	¡ ¢	£ ¤ ¥	¦ § ¨ ©
« ¿ À ª	49.0	•C	
Ring and Ball Softening Point	107	•C	ASTM E28