

Escor € 5100

Ethylene Acrylic Acid Copolymer Resin

ExxonMobil Chemical

€ • , f

Escor 5100 € • , f ... † † , ^ † † † % ... Š < . CE • Ž • • < f ' ' " " , • - , - ~ TM, Š > , ce • % Ž Ÿ | . , f C E α ' ¥ | S ' ' © a « - - < @ . ° ± , 2 3 3 ^ , • ' μ ¶ . 2 3 3 ^ . ' 1 : ' ° » ¼ . ½ © a « . ¾ ¼ , « . • @ % • Ž ' - 2 Ä . ' . A TM Ä ' Ä ' • < ' - < Ä .

Ä Ä Ç	È È Ì	Í Î Ï	Ð Ñ Ò Ó
Ô Õ Ö (Ö Ä Ö × Ø Ö) (190°C/2.16 kg)	8.5	g/10 min	ASTM D1238
Û Ü ı Ů Ű	11.0	wt%	ExxonMobil Method

Ó Ÿ Þ ß
a ä å ¥ | ā ä å , < æ Ä Ç (ç è : FDA, EU, HPFB), é ê ë ì í î ï ð ñ ò ó ô õ ÷ ø . Ä ù | ú û ä ü ý à , Ä þ , ý ú ä ä à , Ä þ ,

β
Excellent results are obtained in extrusion coating at 260°C - 280°C (500°F - 536°F) temperature range. Processing temperatures above 300°C (572°F) may cause resin degradation. To minimize corrosion risk, all exposed metal surfaces in the extruder and die should be made from corrosion resistant metals or nickel/chrome plated. ESCOR should be fed into the extruder after LDPE of a similar or higher melt index. Machines should always be completely purged with LDPE or a suitable cleaning compound before shutdown.